



Technical Data Sheet

Tel.: (011) 882-1200

e-mail: info@smp.co.za

F61- Performance Fuel Enhancer

Solvent Fuel Enhancer

FEATURES

A high concentrate, multi-purpose tank treatment that also cures water related problems in fuel.

Suitable for all types of fuel used in trucks, the marine industry, agricultural and plant machinery. Ideal for use in fuel storage tanks. Suitable for biodiesel.

DESCRIPTION

- Makes water content in the fuel tank combustible.
- Reduces fuel consumption, black smoke and other harmful emissions.
- Completely removes "gumming" or "waxing" from the entire fuel system.
- Improves the lubricating properties of the fuel.
- Cleans and protects from the fuel tank to the combustion chamber.
- Prolongs engine life.

METHOD OF USE

Add contents directly into the fuel tank.

Dosage: 2.5 mL / L of fuel (i.e.: 50 mL / 20L fuel)

PROPERTIES

Appearance	:	Clear, light yellow liquid
Odour	:	Characteristic Solvent
R.D. @ 20°C	:	0,79

PACKAGING

F61-Performance Fuel Enhancer is packed into 150 mL cans.

PRECAUTIONS

Highly Flammable. Vapour accumulation could flash or explode if in contact with a spark or open flame. Avoid contact with skin and eyes or on clothing. In the event of accidental contact with the skin or eyes, rinse with copious amounts of water for at least 15 minutes and seek medical attention. If ingested, give plenty of water to drink and seek immediate medical attention. Do not induce vomiting.

For further information, consult the material safety data sheet.